

60130-1987  
03MRA0008**IN THE CLAIMS:**

Please amend the claims as follows:

1. (CURRENTLY AMENDED) A disc brake assembly comprising:
  - a brake caliper having an outboard side;
  - a brake pad;
  - a pad spring including a spring planar region ~~and a rounded edge~~, wherein the pad spring is substantially clongate and defines a longitudinal direction; and
  - a pad retainer including a retainer planar region ~~having~~ positioned at a first radius ~~for engagement with said spring planar region of the pad spring~~ to restrain radial movement of the brake pad, wherein the pad retainer is secured to the outboard side of the brake caliper at a second radius that is less than the first radius, the pad retainer further including a crook ~~adjacent to the retainer planar region of the pad retainer and the rounded edge of the pad spring~~ at an end of the retainer planar region, wherein a part of the spring planar region engages the pad retainer, and a lateral edge region of the part of the spring planar region adjacent to the outboard side of the brake caliper is rounded.
- 2-3. (CANCELLED)
4. (ORIGINAL) The disc brake assembly according to claim 1 wherein the pad spring is substantially curved.
5. (CURRENTLY AMENDED) The disc brake assembly according to claim 1 further including a backplate, wherein the pad spring further includes radially outwardly curved ends that ~~radially retain~~ limit circumferential movement of the pad spring ~~on~~ relative to the backplate.
6. (ORIGINAL) The disc brake assembly according to claim 5 wherein the backplate includes complementary curved surfaces for abutment with the radially outwardly curved ends of the pad spring.

60130-1987  
03MRA0008

7. (CURRENTLY AMENDED) The disc brake assembly according to claim 1 further including a backplate having a backplate protrusion, ~~and~~ wherein the pad spring further includes an aperture, and wherein the backplate protrusion of the backplate is located in the aperture of the pad spring to prevent axial movement between the pad spring and the backplate.
8. (CURRENTLY AMENDED) The disc brake assembly according to claim 7 wherein the pad spring includes a spring protrusion located around the backplate to ~~prevent~~ assist in preventing axial movement between the pad spring and the backplate.
9. (CURRENTLY AMENDED) The disc brake assembly according to claim 1 wherein the crook has a crook radius that allows the second radius to be less than the first radius, and wherein the crook radius is substantially equal to a lateral edge radius of the ~~rounded~~ lateral edge region of the pad spring, and wherein the lateral edge region of the pad spring is adjacent to the crook.
10. (ORIGINAL) The disc brake assembly according to claim 9 wherein the crook radius is between 4.0 mm and 8.0 mm.
11. (ORIGINAL) The disc brake assembly as related in claim 10 wherein the crook radius is between 5.0 mm and 7.0 mm.
12. (ORIGINAL) The disc brake assembly as recited in claim 11 wherein the crook radius is between 5.25 mm and 6.75 mm.

60130-1987  
03MRA0008

13. (CURRENTLY AMENDED) A disc brake assembly comprising:
- a brake caliper having an outboard side;
  - a brake pad;
  - a pad spring including a spring planar region, ~~a rounded edge~~, radially outwardly curved ends, and an aperture, wherein said pad spring is substantially elongate and defines a longitudinal direction;
  - a pad retainer including a retainer planar region ~~having~~positioned at a first radius ~~for engagement with said spring planar region of the pad spring~~ to restrain radial movement of the brake pad, wherein the pad retainer is secured to the outboard side of the brake caliper at a second radius that is less than the first radius, ~~and wherein the pad retainer further has~~including a crook adjacent to the retainer planar region of the pad retainer and the rounded edge of the pad spring at an end of the retainer planar region, wherein a part of the spring planar region engages the pad retainer, and a lateral edge region of the part of the spring planar region adjacent to the outboard side of the brake caliper is rounded; and
  - a backplate including complementary curved surfaces and a backplate protrusion, wherein the radially outwardly curved ends of the pad spring radially retain the pad spring on the backplate and the complementary curved surfaces of the backplate abut the radially outwardly curved ends of the pad spring, and wherein the backplate protrusion of the backplate is located in the aperture of the pad spring to prevent axial movement between the pad spring and the backplate.
14. (NEW) The disc brake assembly according to claim 1 wherein the brake caliper includes an inboard side, and wherein a second lateral edge region of the part of the spring planar region adjacent to the inboard side of the brake caliper is rounded.
15. (NEW) The disc brake assembly according to claim 1 wherein the pad spring is defined by a length and a width, wherein the part of the spring planar region that engages the pad retainer defines a maximum width of the pad spring.

60130-1987  
03MRA0008

16. (NEW) The disc brake assembly according to claim 15 wherein the pad spring includes longitudinal ends, wherein the longitudinal ends have a reduced width that is less than the maximum width.
17. (NEW) The disc brake assembly as defined in claim 15 wherein the pad spring has a pad spring inboard side and a pad spring outboard side, and the maximum width of the pad spring is defined by an outboard lug portion projecting from the pad spring outboard side and an inboard lug portion projecting from the pad spring inboard side, wherein the lateral edge region is defined by the outboard lug portion.
18. (NEW) The disc brake assembly as defined in claim 17 wherein the inboard lug portion and the outboard lug portion are bent downwardly to provide the lateral edge region and a second lateral edge region, respectively, of the part of the spring planar region that engages the pad retainer.
19. (NEW) The disc brake assembly as defined in claim 17 wherein the pad spring further include a second lateral edge region that is defined by the inboard lug portion.
20. (NEW) The disc brake assembly as defined in claim 1 wherein the part of the spring planar region that engages the pad retainer has a substantially curved cross-section.